

RECEIVED
CENTRAL FAX CENTERAppl. No. 10/790,394
Response to Office Action mailed May 1, 2007

JUL 25 2007

Atty Dkt. No. 114951-006

LISTING OF CLAIMS

This listing of claims replaces all prior versions and listings of claims in the patent application.

Claim 1 (currently amended): A lanyard, comprising:

a load-supporting outer sheath;

a heat shrunk substantially inelastic elongation member extending along an inside of the outer sheath; and

first and second spaced apart connection locations in which the elongation member is secured to the load-supporting outer sheath;

wherein, the elongation member has an un-stretched heat shrunk length between the first and second connection locations substantially shorter than a length of the load-supporting outer sheath between the first and second connection locations;

wherein the heat shrunk elongation member has a first state prior to heat shrinking of being not heat shrunk and a second state after heat shrinking, and wherein the load-supporting outer sheath and the heat shrunk elongation member in the first state are formed substantially simultaneously together as a one-piece webbing; and

wherein the heat shrunk elongation member is elongatable and substantially inelastic in the second state.

Claim 2 (original): The lanyard of claim 1, further comprising a binder yarn and wherein the elongation member is secured to the load-supporting outer sheath by the binder yarn.

Claim 3 (withdrawn): The lanyard of claim 1, wherein the elongation member has elongation yarns and is secured to the load-supporting outer sheath by the elongation yarns and yarns of the load-supporting outer sheath being interlaced together.

Claim 4 (withdrawn): The lanyard of claim 3, further comprising a binder yarn interlaced

Appl. No. 10/790,394
Response to Office Action mailed May 1, 2007

Atty Dkt. No. 114951-006

with the elongation yarns and the yarns of the load-supporting outer sheath.

Claim 5 (withdrawn): The lanyard of claim 1, wherein the elongation member is secured to the load-supporting outer sheath by stitching.

Claim 6 (original): The lanyard of claim 1, wherein at least one of the elongation member and the load-supporting outer sheath is selected from the group consisting of woven materials, braided materials, knitted materials, non-woven materials, and combinations thereof.

Claim 7 (withdrawn): The lanyard of claim 1, wherein a portion of the lanyard has a portion of the elongation member extending to an exterior surface of the load-supporting outer sheath.

Claim 8 (previously presented): A lanyard, comprising:
a tubular-shaped webbing;
heat-shrunk elongation yarns inside of the tubular-shaped webbing, the heat-shrunk elongation yarns being elongatable and substantially inelastic;
first and second spaced apart binder portions in which the heat-shrunk elongation yarns are secured to the tubular-shaped webbing; and
an expansion portion between the first and second binder portions in which the heat shrunk elongation yarns are extensible relative to the tubular-shaped webbing and the tubular-shaped webbing is in a gathered position;
wherein the heat-shrunk elongation yarns has a first state prior to heat shrinking of being not heat shrunk and a second state after heat shrinking, and wherein the tubular-shaped webbing and the heat-shrunk elongation yarns in the first state are formed substantially simultaneously together as a one-piece webbing.

Appl. No. 10/790,394
Response to Office Action mailed May 1, 2007

Att. Dkt. No. 114951-006

Claim 9 (original): The lanyard of claim 8, further comprising a binder yarn and wherein the heat-shrunk elongation yarns are secured to the tubular-shaped webbing by the binder yarn.

Claim 10 (withdrawn): The lanyard of claim 8, wherein the heat-shrunk elongation yarns are secured to the tubular-shaped webbing by the heat-shrunk elongation yarns and yarns of the tubular-shaped webbing being interlaced together.

Claim 11 (withdrawn): The lanyard of claim 10, further comprising a binder yarn interlaced with the heat-shrunk elongation yarns and the yarns of the tubular-shaped webbing.

Claim 12 (withdrawn): The lanyard of claim 8, wherein the heat-shrunk elongation yarns are secured to the tubular-shaped webbing by stitching.

Claim 13 (original): The lanyard of claim 8, wherein at least one of the heat-shrunk elongation yarns and the tubular-shaped webbing is selected from the group consisting of woven materials, braided materials, knitted materials, non-woven materials, and combinations thereof.

Claim 14 (withdrawn): The lanyard of claim 8, further comprising another binder portion in which the heat-shrunk elongation yarns are secured to the tubular-shaped webbing with a different structure than the first and second binder portions.

Claim 15 (withdrawn): The lanyard of claim 8, further comprising a hardware attachment portion having a portion of the heat-shrunk elongation yarns extending to an outside of the tubular-shaped webbing.

Appl. No. 10/790,394

Atty Dkt. No. 114951-006

Response to Office Action mailed May 1, 2007

Claims 16-23 (cancelled).

Claim 24 (previously presented): The lanyard of claim 1, wherein relative lengths of the load-supporting outer sheath and the heat shrunken elongation member in the first state are adjusted by heat treatment of the one-piece webbing.

Claim 25 (cancelled).

Claim 26 (previously presented): The lanyard of claim 8, wherein relative lengths of the tubular-shaped webbing and the heat-shrunk elongation yarns in the first state are adjusted by heat treatment of the one-piece webbing.

Claim 27 (new): The lanyard of claim 1, wherein the heat-shrunken elongation member is free from being secured to the load-supporting outer sheath between the first and second connection locations.

Claim 28 (new): The lanyard of claim 8, wherein the heat-shrunken elongation yarns are secured to the tubular-shaped webbing at spaced apart connection locations and the heat-shrunken elongation yarns are free from being secured to the tubular-shaped webbing between the connection locations.